

## PRODUCT INFORMATION SHEET

### LOW FOAM TRUCK WASH

#### PRODUCT DESCRIPTION

Low Foam Truck Wash is specifically formulated for the removal of grime from trucks, machinery and plant equipment. Low foam truck wash can be used through automatic dosing systems such as automated truck wash units, high pressure cleaners and sprayers where a low foaming wash is desired. Low Foam Truck Wash is suited for everyday equipment washing and is safe on most surfaces including paint, aluminium, steel, plastic and rubber.

#### DIRECTIONS FOR USE

##### Recommended Dilution: 50mls per 1L of water

Spray solution over vehicle with spray gun of high pressure. Allow to soak for 10 minutes. Hose off solution under pressure. Machines of high pressure may use lower dilutions of around 20-30ml per litre. Can be brushed on for heavily soiled areas.

#### FIRST AID & SAFETY

This product is considered hazardous as it will irritate the eyes. Wear gloves and if necessary wear eye protection when handling. Keep out of reach of children. If swallowed seek medical advice. If poisoning occurs contact a Doctor or the Poisons Information Centre. If swallowed do NOT induce vomiting, give water. If skin contact occurs wash affected area and remove clothing. If in eyes, hold eyes open and flood with water for a minimum of 15 minutes. Call a Doctor.

Refer to Safety Data Sheet for more information.

#### FEATURES & BENEFITS

- Low Foaming Formulation
- Safe on most surfaces
- Non Flammable and non-corrosive
- Ideal for automated units or high volume washing.

#### PACK SIZES

20 Litre: NCLFTW20

200 Litre: NCLFTW200

